



KRMG

60 mm

Key features

- Compact and rugged design
- 'No spindle' concept
- Easy to integrate



| Characteristics | Unit | KRMG |
|------------------------|---------|---|
| Printing Speed (max) | mm/s | 80 |
| Printing Width | mm | 48 |
| Resolution | dot/mm | 8 |
| Number of Dots | dot | 384 |
| Number of Columns | column | 24 or 42 |
| Character Size | dot*dot | 16 x 24 or 9 x 24 |
| Resident Code Page | --- | CP 437 |
| Bar Code Type | --- | Code 39, 93, 128, Interleaved 2/5, UPC-A, UPC-E, JAN8 (EAN8) & JAN13 (EAN13), Codabar, PDF417 |
| Paper Width | mm | 60 |
| Paper Roll Diameter | mm | 120 |
| Paper Thickness | µm | 60 to 80 |
| Paper Loading | --- | Auto loading |
| Operating Voltage | VDC | 12 or 24V |
| Power Consumption | W | 55 |
| Head Pulse Life | pulse | 1*10 ⁸ |
| Mechanical Reliability | Km | 50 |
| Dimensions (W*D*H) | mm | 125 x 168 x 112 |
| Weight | g | 1525 |
| Operating Temperature | °C/F | 0 to 50 / 32 to 122 |
| Operating Humidity | % RH | 20 to 85 (non condensing) |
| Cutter | --- | Auto cutter (full and partial cuts) |
| Cutter Life | cuts | 1 Million |
| Data Buffer | Kbytes | 4 |
| Interface | --- | RS232 or parallel IEEE 1284 (with sub - D25 connector) |
| Driver | --- | Windows™ 98 / 00 / XP / Vista / CE - Linux |
| CEM & Safety Standards | --- | UL60950-1, CSA 22.2-60950-1, IEC60950, CE Class B, FCC Class B, C-Tick |
| Sensors | --- | Paper low, paper out |
| Accessories | --- | Power supply |

